

(19) World Intellectual Property Organization

International Bureau





(10) International Publication Number WO 2004/021455 A1

(51) International Patent Classification7: H01L 31/0224

(21) International Application Number:

PCT/CA2003/001278

(22) International Filing Date: 21 August 2003 (21.08.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 102 39 845.3

29 August 2002 (29.08.2002)

- (71) Applicant (for all designated States except US): DAY4 ENERGY INC. [CA/CA]; 1600 - 609 Granville Street, Canaccord Tower, Vancouver, British Columbia V7Y 1C3 (CA).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): RUBIN, Leonid, B. [RU/CA]; Suite 303, 1838 Nelson Street, Vancouver, British Columbia V6G 1N1 (CA). RUBIN, George, L. [CA/CA]; Suite 801, 1845 Robson Street, Vancouver, British Columbia V6G 1E4 (CA).


- (74) Agents: FETHERSTONHAUGH & CO. et al.; Box 11560, Vancouver Centre 650 West Georgia Street, Suite 2200 Vancouver, British Columbia V6B 4N8 (CA).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC. LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

[Continued on next page]

(54) Title: ELECTRODE FOR PHOTOVOLTAIC CELLS, PHOTOVOLTAIC CELL AND PHOTOVOLTAIC MODULE



(57) Abstract: An electrode is described for contacting an electrically conductive surface, in particular for contacting at least one surface of a photovoltaic element wafer 3, the electrode comprising an electrically insulating optically transparent film 10, an adhesive layer 11 provided on one surface of said film 10, and a first plurality of substantially parallel, electrically conductive wires 5' being embedded into the adhesive layer 11, a part of the surfaces of said wires 5' protruding from the adhesive layer 11 and at least on the surface protruding from the adhesive layer 11 being covered by a coating 2 consisting of an alloy with a low melting point, wherein the wires 5' of the first plurality are electrically connected to a first terminal bar 20. A plurality of said electrodes may be formed as an endless, continuous strip, which can be cut to a length corresponding to that of an array of adjacent photovoltaic elements 3 to be connected for forming a PV module, wherein the wires 5' running in longitudinal direction of the strip are cut at distances corresponding to the distances of the PV cells. A PV cell or a PV module comprising at least one electrode 16 or one electrode strip 16 as described above may comprise one or more photovoltaic cells 3 with an electrically conductive, antireflective, optically transparent coating 4 on at least one of its surfaces, the wires 5' of the first plurality being soldered onto the coating 4 and onto the respective terminal bars 20 or terminal frames 17 by means of the alloy 2.